

PosiTest[®] DFT

Coating Thickness Gage

New

Ideal for...

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

2 Models...

Ferrous for STEEL

Combo for ALL METALS



simply
measures

DeFelsko[®]
The Measure of Quality

PosiTest[®] DFT

Coating Thickness Gage

Actual Size

Two Models

- **PosiTest DFT Ferrous**
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.



Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage

Specifications

Measurement Range	0 – 40 mils	0 – 1000 µm
Accuracy	±(0.1 mils + 3%)	±(2µm + 3%)
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
Weight	2.5 oz.	70 g



Gage Comes Complete with built-in probe, plastic shims, hard shell storage case, AAA battery, instructions and one (1) year warranty.

Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/E376/G12, BS3900-C5, SSPC-PA2 and others. *Certificate of Calibration traceable to NIST available.*

© DeFelsko Corporation USA 2004. All Rights Reserved. Technical Data subject to change without notice. U.S. Patent # Re.35,703 • Printed in U.S.A. PDFT.v.LW/W0404