



# Temperature Assemblies

## Temperature Transmitter with Sensor

RTD • Model TR701

### Temperature Transmitters

---

#### Application

Industrial temperature assembly includes sensor, protection head and analog transmitter. Designed for installation directly into tanks, piping or ovens, the TX701 features 1/2" NPT fitting welded to a stainless steel stem. Factory calibrated to provide a 4-20 milliamp 2-wire current output. The current output virtually eliminates electrical interference from line noise and provides for signal transmission over long distances using standard wire. This design eliminates the need for long runs of expensive thermocouple wire or extension wire.

The TR701 measures the temperature using a platinum 100 ohm RTD sensor. The RTD provides a higher accuracy measurement of temperature, the transmitter output of the TR701 output is linearized to temperature.

The TC701 measures the temperature with a type K (nickel-chromium/nickel-aluminum) thermocouple. The thermocouple is more suited to rugged applications such as temperature measurement in high vibration areas (diesel engines, compressors & pumps). The analog output from the transmitter is linear to the microvolt output of the thermocouple.

#### Accuracy

TR701

Pt100 Class B  $\pm 0.54^{\circ}\text{F}$  @  $32^{\circ}\text{F}$

Linearity error: 0.1% of range

#### Ranges

TR701

0-150°F, 0-250°F, 0-500°F, 0-750°F, 0-1000°F



### Standard TR701 Features

#### Sensor

TR701 Type: RTD Pt100 3-wire

#### Stem Material

316Ti Stainless Steel

#### Standard Stem Lengths

4", 6", 9", & 12"

#### Stem Diameter

0.25"

#### Protection Head

Material: Aluminum

Process Connection: 1/2" NPT male

Electrical Connection: 1/2" NPT female

Weatherproof: NEMA 4

#### Temperature Transmitter T21

(Optional transmitters available on request)

#### T21 Output

4-20mA

#### T21 Power Requirements

14- 30 Vdc

#### T21 Transmitter Environmental

Ambient Temperature: -40°F to 185°F (-40°C to 85°C)

Humidity: 0-95% non-condensing

Vibration: 10 Hz to 2 KHz, 5g per DIN IEC 68 2-6

**ATE TR701**  
**(ATE70)**

---

## Specifications

### TR701 RTD Assembly

**Standard Ranges :**

0.. 150°F, 0.. 250°F, 0.. 500°F, 0.. 750°F, 0.. 1000°F

**Output**

4-20mA

**Sensor**


RTD Pt100 (Alpha 0.00385)

**Configuration**

3-wire

**TR701 Wiring**

Connect power (14 to 30Vdc) to  
Terminals 1 & 2



THE MEASURE OF  
**Total Performance™**

---

**Ordering Information:**

State computer part number (if available) / type number / size / range / connection size and location / options required.

Specifications given in this price list represent the state of engineering at the time of printing. Modifications may take place and the specified materials may change without prior notice

05/01



**WIKA Instrument Corporation**

1000 Wiegand Boulevard

Lawrenceville, Georgia 30043-5868

Tel: 770-513-8200 Fax: 770-338-5118

<http://www.wika.com> e-mail: [info@wika.com](mailto:info@wika.com)